

# CONTAINER SIZE

TYPE	MAX G.WEIGHT	TARE WEIGHT	EXTERNAL(MM)			INTERNAL(MM)			INSIDE CAP (M3)
			LONG	WIDE	HIGH	LONG	WIDE	HIGH	
12' DRY	6,380	1,380	3,658	2,438	2,591	3,572	2,302	2,372	19.500
12' R/F	10,000	2,185	3,658	2,440	2,590	3,070	2,235	2,250	15.980
20' DRY	24,000	2,240	6,058	2,438	2,591	5,899	2,352	2,385	33.100
20' I/S	24,000	3,030	6,058	2,438	2,591	5,850	2,254	2,323	30.600
20' R/F	20,320	3,180	6,058	2,438	2,591	5,392	2,254	2,256	27.400
20' H/H	18,000	2,000	6,058	2,438	1,296	5,899	2,352	1,192	
40' DRY	30,480	3,700	12,192	2,438	2,591	12,035	2,350	2,392	67.700
40' H/C	30,480	3,760	12,192	2,438	2,896	12,035	2,350	2,703	76.450
40' R/F	32,480	4,440	12,192	2,438	2,591	11,563	2,286	2,189	57.800
40' H/R	33,000	4,140	12,192	2,438	2,896	11,563	2,286	2,535	67.000
40' F/R	40,480	5,130	12,192	2,438	2,560	12,062	2,250	1,950	